

The timber treatment operations of

Calders & Grandidge

194 London Road Boston Lincs. PE21 7HJ

have been assessed and certified as meeting the requirements of the Wood Protection Association

Benchmark Quality Approval Scheme

for the preservative impregnation of the softwood components listed below in accordance with the standards and practices defined in the WPA Manual - Industrial Wood Preservation:

Creosote (Scots pine and Douglas fir). AC 500 (Scots pine):

Poles
Fence posts (75 x 75 – 75 x 150 mm)
Gate posts (150 x 150 – 200 x 200 mm)
Stakes (50 x 75 – 225 x 250 mm)
Peeled stakes (creosote only)
Round (machined) posts (85 – 100 mm) (creosote only)
Sleepers – crossings/bearers, (Maritime and Scots pine) (130 x 250 mm, 130 x 300/305 mm, 150 x 300 mm)

BS 8417 Use Class 3 (exposed to weather but not in ground contact)

Fence rails (38 x 87 – 50 x 150 mm)
Laminated sections (Scots pine only (70 x 95 mm)

Detailed clarification of the scope of this certificate and the applicability of the Benchmark quality scheme is available from the Wood Protection Association.

This scheme does not confirm compliance of the preservative used with British Standard or other specifications - that is the responsibility of the preservative manufacturer.

This certificate of conformity is valid from the date indicated for twelve months and remains valid subject to satisfactory surveillance visits.

Authorised by:



Chris Coggins
WPA Quality & Standards Director



Wood Protection Association

Wood Protection Association
5C Flemming Court
Castleford, West Yorkshire
WF10 5HW

contact@thewpa.org.uk
www.thewpa.org.uk

Benchmark

APPROVED TREATER



Certificate firm no. TW201104

Date of first issue: 13/12/2011

Date of this issue: 2 December 2019

Issue No. 7